HeatLink is pleased to introduce it's new line of colored PureLink[®] PEX-a tubing for easy identification and improved performance.

HeatLink Red & Blue PEX-a Tubing Advantages:

- Clean & non-toxic
- Resists scaling & corrosion
- Quiet no water hammer noise
- Equalized pressure drops, minimize hot or cold surges
- Durable
- Reliable installation
- Low friction losses
- Meets or exceeds all applicable North American approvals including:
 - » Domestic hot water continuous recirculation
 - » CAN/ULC S102/2010 and ASTM E84 plenum acceptance
- Flexible tubing means fewer fittings
- Freeze resistant
- UV stabilized & chlorine resistance
- 25 year system warranty

The HeatLink system approach ensures that all of our potable products can be used together to create a reliable and easy to install system that meets all of your installation needs.

Our colored-wall PEX-a tubing continues the tradition of usability and dependability that you've come to trust.

For over 25 years HeatLink Group has supplied radiant heating and cooling systems, PEX-a plumbing, and hydronic panels for the residential and commercial building markets across North America. As a fully integrated plumbing and heating manufacturing company, HeatLink provides a complete system approach backed by a reputation for quality, innovation and industry leadership.



Colored Wall PEX-a Tubing

www.heatlink.com

HeatLink and PureLink are either registered trademarks or trademarks of HeatLink Group In L3280

December 9, 2020

Printed in Canada

PureLink[®] Plus PEX-a Tubing

Cross-linked polyethylene tubing; crosslinking occurs during the extrusion process resulting in more uniform and higher degree in cross linking, as well as significantly improved material properties, such as flexibility, chemical resistance, and durability.

Colored PEX-a Tubing

Size	Length	Stk #	
Coils		Blue Wall	Red Wall
1⁄2"	100'	20105BW	21105RW
	300'	20305BW	21305RW
3⁄4 "	100'	20122BW	21122RW
	300'	20322BW	21322RW
1"	100'	20128BW	21128RW
	300'	20328BW	21328RW
Straight Lengths		Blue Wall	Red Wall
1⁄2"	20' × 20	20205BW	21205RW
3⁄4 "	20' × 10	20222BW	21222RW
1"	20' × 5	20228BW	21228RW

Red and Blue PEX makes identification of hot and cold lines easy on any job site.